

Batteries Plus Bulbs stocks a full assortment of Streamlight product including the popular ProTac, Stinger & Strion. Streamlight flashlights are the ultimate choice for public safety, military and industrial markets. Streamlight is one of the most recognized professional flashlight manufacturers in the market known for quality and proven performance. We also offer a full selection of accessories including replacement batteries, chargers, wands, filters and more. While our stores only stock the most popular items, a full assortment of product and accessories can be ordered.





Benefits

- Built for high durability and performance
- Strongest warranty in the flashlight market
- Wide selection of rechargeable solution for the lowest possible cost of ownership
- Wider available variety of specialty lighting tools than any other manufacturer





High Performance



Reliable and Durable



Water Resistance IPX4 / IPX7



Limited Lifetime Warranty



| PROJECT NAME: |
|---------------|
| CATALOG # |
| FIXTURE TYPE |
| NOTES |

| | STR61304 | | | STR61400 | | STR61700 | | STR61702 | | STR74301-STR74302-STR74303 | | | |
|-------------------|----------|---------------|--------|-----------------|--------|---------------------------------|---------------|---------------------------------|---------|----------------------------|----------|----------|--|
| Modes | High | Medium | Low | High | Low | High | Low | High | Low | High | Medium | Low | |
| Output | 635 | 105 | 20 | 50 | 10 | 180 | 180 35 | | 35 | 260 | 130 | 65 | |
| Runtime | 1.75 hrs | 8 hrs | 36 hrs | 5.5 hrs | 25 hrs | 2 hrs | 2 hrs 9.5 hrs | | 9.5 hrs | 2 hrs | 4 hrs | 7.5 hrs | |
| Distance | 184 m | 76 m | 33 m | 66 m | 33 m | NA- Ideal for close up tasks | | NA- Ideal for close up tasks | | 200 m | 141 m | 100 m | |
| Intensity | 8,500 cd | 1,450 cd | 280 cd | 1,100 cd | 285 cd | | | | | up tasks | 5,000 cd | 2,500 cd | |
| Water Resistance* | | IPX4 | | IPX7 | | IPX4 | | IPX4 | | IPX4 | | | |
| Impact Resistance | 1 m | | 2 m | | 2 m | | 2 m | | 2 m | | | | |
| Warranty | Limite | d Lifetime Wa | rranty | 2 Year Warranty | | 2 Year Warranty | | 2 Year Warranty | | 2 Year Warranty | | | |

| | STR75429- | STR75430-9 | STR75431 | STR75711 and STR75713 | | | | STR75761 | | STR75811 and STR75813 | | | |
|-------------------|------------------------------------|------------|-----------------|-----------------------|-----------|-----------------|-----------|-----------|-----------------|-----------------------|-----------|----------|--|
| Modes | High | Medium | Low | High | Medium | Low | High | Medium | Low | High | Medium | Low | |
| Output | 800 | 400 | 200 | 400 | 200 | 100 | 800 | 400 | 200 | 350 | 175 | 85 | |
| Runtime | 1.5 hrs | 2.5 hrs | 3 hrs | 2 hrs | 3.75 hrs | 7.25 hrs | 1.5 hrs | 2.5 hrs | 5 hrs | 2 hrs | 3.75 hrs | 7.25 hr | |
| Distance | 310 m | 219 m | 155 m | 310 m | 219 m | 155 m | 438 m | 310 m | 219 m | 310 m | 219 m | 155 m | |
| Intensity | 24,000 cd | 12,000 cd | 6,000 cd | 24,000 cd | 12,000 cd | 6,000 cd | 48,000 cd | 24,000 cd | 12,000 cd | 24,000 cd | 12,000 cd | 6,000 cd | |
| Water Resistance* | IPX4 | | | IPX4 | | | IPX4 | | | IPX4 | | | |
| Impact Resistance | 1 m | | | 1 m | | | 3 m | | | 1 m | | | |
| Warranty | Warranty Limited Lifetime Warranty | | 2 Year Warranty | | | 2 Year Warranty | | | 2 Year Warranty | | | | |

| | STR75863 | | | STR76111 | | | STR88030 | | STR88031 | | STR88033 | | |
|-------------------|-----------|-----------------|-----------|-----------|---------------------------|----------|----------|---------------------------|----------|---------------------------|----------|---------------------------|--|
| Modes | High | Medium | Low | High | Medium | Low | High | Low | High | Low | High | Low | |
| Output | 800 | 400 | 200 | 385 | 195 | 95 | 275 | 22 | 350 | 30 | 250 | 18 | |
| Runtime | 1.5 hrs | 2.5 hrs | 5 hrs | 2 hrs | 3.75 hrs | 7.25 hrs | 2 hrs | 24 hours | 3.25 hrs | 35 hrs | 2 hrs | 43 hrs | |
| Distance | 438 m | 310 m | 219 m | 322 m | 228 m | 161 m | 143 m | 41 m | 159 m | 49 m | 130 m | 40 m | |
| Intensity | 48,000 cd | 24,000 cd | 12,000 cd | 36,000 cd | 13,000 cd | 6,500 cd | 5,100 cd | 420 cd | 6,300 cd | 600 cd | 4,250 cd | 400 cd | |
| Water Resistance* | IPX4 | | | IPX4 | | | IPX7 | | IPX7 | | IPX7 | | |
| Impact Resistance | 3 m | | | 3 m | | | 2 m | | 2 m | | 2 m | | |
| Warranty | 2 | 2 Year Warranty | | | Limited Lifetime Warranty | | | Limited Lifetime Warranty | | Limited Lifetime Warranty | | Limited Lifetime Warranty | |

| | STR88039 | | STR88 | 040 | s | ΓR88060 | | STR88 | 3061 | STR88062 | | STR88064 | | |
|-------------------|----------------|-------------|-----------------|--------|---------------------------|----------|--------|-----------------|--------|------------------------------|--------|---------------------------|-----------|----------|
| Modes | High | Low | High | Low | High | Medium | Low | High | Low | High | Low | High | Medium | Low |
| Output | 130 | 20 | 750 | 35 | 2200 | 600 | 60 | 350 | 40 | 500 | 40 | 1,000 | 400 | 65 |
| Runtime | 1.75 hrs | 13 hrs | 1.25 hrs | 18 hrs | 1.5 hrs | 4.25 hrs | 40 hrs | 1.5 hrs | 14 hrs | 2.75 hrs | 30 hrs | 1.25 hrs | 3.5 hrs | 23 hrs |
| Distance | 70 m | 30 m | 270 m | 60 m | 346 m | 182 m | 56 m | 160 m | 53 m | 165 m | 49 m | 330 m | 200 m | 80 m |
| Intensity | 1,230 cd | 230 cd | 18,300 cd | 900 cd | 30,000 cd | 8,300 cd | 800 cd | 6,400 cd | 720 cd | 6,800 cd | 600 cd | 27,100 cd | 10,000 cd | 1,600 cd |
| Water Resistance* | IPX7 | | IPX7 | | IPX7 | | | IPX7 | | IPX7 | | IPX7 | | |
| Impact Resistance | 2 : | m | 1 m | | 1 m | | | 2 m | | 2 m | | 2 m | | |
| Warranty | Limited Lifeti | me Warranty | 2 Year Warranty | | Limited Lifetime Warranty | | | 2 Year Warranty | | Limited Lifetime Warranty | | Limited Lifetime Warranty | | |

*IPX4 – water-resistant

IPX7 – water-proof, submersion at 1 meter for up to 30 minutes

